



Heavy Duty Bain Maries with Hot Cupboard

Sliding Doors on both sides are available for pass-through

Use as Wet or Dry, **Switch Between Wet and Dry Well Bain Marie Operation.**

Versigen were the originators of a Bain-marie that could be either wet or dry heat. This type of system was designed to offer flexibility and was developed to eliminate the need to fit a low water level warning system or the expense of replacing burned out elements. Wet heat water level is an economic 20 mm deep, complete with drain valve and swing out run off tube for easy emptying/cleaning.

Our Premier Bain Maries with Hot Cupboard are available in 4 lengths designed to accommodate 1/1 GN pans, Excellent for pre-heating plates and dishes, as well as the temporary storage of pre-cooked food. These units incorporate a very efficient heating system, additional to the fully enclosed heating elements fitted under the Bain Marie Well. Excess residual hot air from the hot cupboard is also used to maintain temperature.

Features
Heavy duty bain marie / hot cupboard designed for commercial catering
Bain Marie top in stainless steel with opening well to take gastronorm containers
Bain Marie opening has a raised lip all round to prevent the ingress of debris into the well and to make it easy to remove the gastronorm containers (no need to use implements to raise the pan edge for lifting).
Unprecedented even flow of hot air re-circulates throughout the hot cupboard
Bain Marie has 3 position energy regulator
Modern insulating methods help keep running costs low reducing the carbon footprint
Features satin and bright polished stainless steel
Thermostatically controlled hot cupboard with fan assisted removable heating unit, 30°- 110°C
Castors fitted as standard
Legs can be supplied, at no extra cost, but must be stated at time of ordering
Option: sliding doors on both sides of the hot cupboard. Must be included with order. Add DBS to model code

Model Specifications

Model	Length	Depth	Height	Weight	Amp	Power (kW)
HB2	947	700	910	65	15	2.4
HB3	1275	700	910	81	15	2.9
HB4	1603	700	910	100	15	2.9
HB5	1931	700	910	118	20	3.7
HB2DBS	947	700	910	65	15	2.4
HB3DBS	1275	700	910	81	15	2.9
HB4DBS	1603	700	910	100	15	2.9
HB5DBS	1931	700	910	118	20	3.7

For easy cleaning all units are now fitted with castors as standard. Feet can be supplied, at no extra cost, but must be stated on order
All models supplied with a 2m long power cable and plug single phase.
Note - wet wells require manual filling.