



## 2 Shelf Drop-in Refrigerated Display with Square Glass and Roller Shutter

Chilled display units incorporating a cold well and 2 glass display shelves. The unique Versigen innovative “Polar Air Stream” system provides a constant, recirculating cold air curtain completely enveloping the food displayed. Holding pre-chilled food at a safe, regulated temperature while retaining taste and freshness. Perfect for sandwiches, fruit, yogurts and cold drinks. Self-contained units with accurate, digital control, automatic defrost, high pressure warning and automatic condensate evaporation. The Refrigeration System is housed underneath in a tidy, compact cradle. Utilising a highly efficient, naturally occurring, hermetically sealed, hydrocarbon gas type R290 as standard - reducing carbon footprint and energy consumption.

| Features                                                                                                                                  |
|-------------------------------------------------------------------------------------------------------------------------------------------|
| Condensing unit set at 90°. Removes the need for unsightly vents in the front panels of serveries and counters.                           |
| Digital thermostat & temperature controller.                                                                                              |
| Sliding rear double glazed doors.                                                                                                         |
| Advanced air flow design with unique polar airstream technology.                                                                          |
| Controls conveniently positioned in the gantry hood.                                                                                      |
| Efficient, ozone friendly hydrocarbon refrigeration.                                                                                      |
| Long life, low energy LED.                                                                                                                |
| Maintaining the core product temperature of pre-chilled food below 5°C in ambient condition not exceeding 25°C and 60% relative humidity. |
| Automatic condensate water evaporation [no need to empty drip trays].                                                                     |
| Automatic defrost control.                                                                                                                |
| 24 hour operation.                                                                                                                        |
| Fully insulated.                                                                                                                          |
| Plenum duct to aid onsite ventilation and installation.                                                                                   |

| Optional Extras                                                                                              |
|--------------------------------------------------------------------------------------------------------------|
| Additional air flow kit [In-line fan and flexi ductkit for difficult non-standard installations] (Code: DRA) |
| Front Roller Blind (add "RB" to end of model code)                                                           |

## Model Specifications

| Model   | Length | Depth | Height | Weight | Amp | Power (kW) |
|---------|--------|-------|--------|--------|-----|------------|
| D2RDLSA | 830    | 660   | 645    | 119    | 10  | 1.5        |
| D3RDLSA | 1158   | 660   | 645    | 140    | 10  | 1.5        |
| D4RDLSA | 1486   | 660   | 645    | 158    | 10  | 2.0        |
| D5RDLSA | 1814   | 660   | 645    | 179    | 10  | 2.5        |